Estimation Sheet of Seal Peel Melting Tank

Entry date:

□llser	Name of a	a person in charge
	npany	
Fax ni	mhar	
I ax IIu	mbei	
		2 Change in voltage
0.V, 900.W/\		2. Change in voltage ☐ No change
□ Very small size (100 V, 800 W) □ Small size (100 V, 1.2 kW)		☐ No change ☐ Single-phaseV
☐ Middle size (Single-phase, 200 V, 2.6 kW)		☐ Single-phaseV
☐ Large size (Three-phase, 200 V, 2.0 kW)		(Name of a country in which a type
□ Custom-made size		used:
		Power supply can be changed to
Quantity: Seal peel solvent: Enter it in "3. Option" for a single item. Enter it in "5. Custom-made size" for custom-made size.		overseas specifications.
		(Example: Three-phase 380 V for Indonesia)
		,
		4. Investigation status
Wallit to fileti a seai peel ili auvanioo oi tuili on a rioa.	el al life end or won	□ Investigation of existing tank
☐ Time limit OFF : This function automatically shuts down a heater when the set time is completed.		replacement
		☐ Stage of information collection
·		☐ Budget inclusion in the next quart
: Standard products (Suitable for rust prevention of al	out one vear)	☐ Scheduled introduction date
		/
	1	
	0. WOI KPIECE U.S.	;u
MIS .	Products:	
:	1 Toddets.	Example: Gear, cutter, and c
:	NA - t - of - L - o lite o	
:	Material quality:	Example: SKD11 (Die ste
		Example. SND11 (Die Ste
	Product dimensio (W × L ×	
1	$(VV \times I \times I)$	
<i>!</i>	(** * = *	11).
	Intended use:	
	,	11).
er leg	,	, <u> </u>
er leg may not be able to meet your request. (We	,	
er leg	Intended use:	Example: Rust prevention and protection of produc
er leg	Intended use:	Example: Rust prevention and protection of produc
er leg	Intended use:	Example: Rust prevention and protection of produc
er leg	Intended use:	Example: Rust prevention and protection of produc
er leg	Intended use:	Example: Rust prevention and protection of produc
er leg	Intended use:	Example: Rust prevention and protection of produc
er leg	Intended use:	Example: Rust prevention and protection of produc
er leg	Intended use:	Example: Rust prevention and protection of produc
1 2 2	Fax nu Fax nu 10 V, 800 W) 1.2 kW) -phase, 200 V, 2.6 kW) ohase, 200 V, 4 kW) ter it in "3. Option" for a single item. Enter it in "5. Custom de size. : This function (with a selector switch) can turn on and want to melt a seal peel in advance or turn off a heat : This function automatically shuts down a heater whe completed. : Standard products (Suitable for rust prevention of ab : MIL compliant products (Suitable for long-term rust p	Store/Trading company Fax number